





Shredder Model	CP316S2i	CP320S2i	CP422S2i	CP430S2i
				
TECHNICAL INFORMATION				
Unit Type	Free-standing	Free-standing	Free-standing	Free-standing
Max thickness of cardboard to be shredded	12mm	15mm	18mm	20mm
Max width of cardboard to be shredded	320mm	320mm	420mm	420mm
Voidfill produced per hour	1-2 metres ³	2-3 metres ³	4-6 metres ³	7-10 metres ³
Suitable Dust Extraction Unit	✗	W796	W791	W791
Emergency Stop Button	✓	✓	✓	✓
Suitable for	Suits a variety of warehouse operations. An ideal option for small to medium businesses	Suits a variety of warehouse operations. An ideal option for small to medium businesses	Ideal industrial machine with single and three phase plug. Suitable for high volume usage	For larger businesses due to the cubic metres of void per hour. Shreds from thin to very thick cardboard

Dust Extractor Models	W796	W791
		
TECHNICAL INFORMATION		
Motor	750W (1hp)	1500W (2hp)
Voltage	240v	240v
Flowrate	1000m ³ /hour	2000m ³ /hour
Bag Capacity	70 litres	148 litres
Weight	37kg	60kg
	<i>Only for use with CP320S2i</i>	<i>Only for use with CP422S2i and CP430S2i</i>